



FEATURES

- Compatible with 10/100/1000Mbps Ethernet
- 10/100/1000 Mbps half/full duplex PassThrough Data Rates
- Compatible with IEEE802.3af and IEEE802.3at
- Extends the range of PoE and Ethernet an additional 100 meters
- No additional power supply required
- Automatically detects and protects PoE equipment from incorrect installation
- Full-rate network throughout the whole extended distance
- Compact size, Wall-Mountable design
- Easy plug-and-play installation

VT-P2EX Specifications	
Channels	1
Pass-Through Data Rates	10/100/1000 Mbps half/full duplex
Power over Ethernet input	PinAssignment and Polarity: Both 1/2 (-), 3/6 (+) and 7/8 (-), 4/5 (+)
Power over Ethernet Output	PinAssignment and Polarity: 1/2 (-), 3/6 (+) Output Power: up to 22W
Indicators	LED RJ45 Connector Power indicator: PoE enabled Network indicator: Link/Act
Connectors	Shielded RJ-45, EIA568Aand 568B
Network cables	Category 5 (or higher)
Mounting	Wall of shelf
Operating Environment	14-113F (-10~45c) / 10% ~ 90% RH
Regulatory Compliance	IEEE 802.3af (PoE), IEEE 802.3at (PoE+)
Dimensions	5.71" x 2.36" x 1.57" (145mm x 60mm x 40mm)