

VTC-EL52H

Vandal/Weather Resistant
Elevator Camera



FEATURES

- 1/3" Color CCD Image Sensor w/550 TV Lines
- Camera Mounted a 3-Axis Adjustable Bracket to Achieve the Perfect Viewing Angle
- 2.97mm Fixed Iris Lens Included
- Minimum Illumination of 0.5 Lux
- Aluminum and Polycarbonate Vandal Resistant Enclosure with IP-66 Weather Resistance

VTC-EL52H

Vandal/Weather Resistant
Elevator Camera

Detailed Specifications

Image Device	1/ 3 inch interline transfer CCD
Resolution	More than 550 TV Lines
Scanning System	2:1 Interlace
Synchronisation	INT
Frequency	Horizontal:15.734 KHz Vertical :59.94 Hz Horizontal: 15.625 KHz Vertical : 50.00 Hz
Total Pixels	811(H) x 508(V)
Effective Pixels	768(H) x 494(V)
Video Output	1.0Vp-p/75(Video 0.714Vp-p Sync 0.286Vp-p) 1.0Vp-p/75 (Video 0.7 Vp-p Sync 0.3Vp-p)
S/N (Y signal)	50dB (AGC Off)
Min. Illumination	0.5Lux 40 IRE (F1.2)
Lens	2.97mm Fixed Iris (Optional lenses available)
White Balance	ATW / AWB / FIXED / MANUAL(1,800°K~10,500°K)
Electronic Shutter Speed	AUTO / MANUAL(1/60~1/100,000) AUTO / MANUAL(1/50~1/100,000)
O.S.D	Built-in
Motion Detection	ON / OFF (64 Programmable Zones)
BLC	ON / OFF (64 Programmable Zones)
Mirror	Built-in (Horizontal Image Inversion)
Privacy Function	ON / OFF (4 Programmable Zones)
Operation Temperature	-10°C ~ +50°C / 30~90% RH
Power Source	DC12V
Power Consumption	Max.120mA
Weight	13.4 oz. (380g)



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355