



FEATURES

- Provides 16 10/100Base-TX ports / 1 Gigabit /STP Fiber Combo (SFP or RJ45) / 1 Gigabit RJ-45
- 200 Watt PoE Power Budget
- Conforms to PoE Standard: IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at
- High back-plane bandwidth 7.2Gbps
- IEEE802.3x Flow control
- EMI standards complies with FCC, CE class B
- Surge Protection for Power and Data Ports

| VT-16P200 Specifications | |
|--------------------------------|--|
| Ethernet Speed | 16x PoE Ports: 10/100Mbps / G1 (combo) 10/100/1000Mbps & 1.25Gbps / G2 10/100/1000Mbps |
| Ethernet Transmission Distance | 328 feet (100 Metres) |
| Ethernet Standard | IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at |
| Switching capacity | 7.2G |
| Transfer Rate | 14,880 pps @ 10Mbps / 148,800 pps @ 100Mbps / 1,488,000 pps @ 1000Mbps |
| MAC Address | 4K MAC address table |
| Power Supply | Built-In Power Supply |
| Voltage Range | 100~240 VAC |
| Power Consumption | 200W for 16 PoE |
| Working Temperature | 32°~104°F (0°~40°C) / 20~85% RH |
| Dimensions (W x H x D) | 11.02" x 7.09" x 1.73" (280 x 180 x 44mm) |