



FEATURES

- Provides 16 10/100Base-TX ports / 1 Gigabit /STP Fiber Combo (SFP or RJ45) / 1 Gigabit RJ-45
- 200 Watt PoE Power Budget
- Conforms to PoE Standard: IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at
- High back-plane bandwidth 7.2Gbps
- IEEE802.3x Flow control
- EMI standards complies with FCC, CE class B
- Surge Protection for Power and Data Ports
- Includes Rack Ears
- 3-Year Warranty

VT-16P200 Specifications

Ethernet Speed	16x PoE Ports: 10/100Mbps / G1 (combo) 10/100/1000Mbps & 1.25Gbps / G2 10/100/1000Mbps
Ethernet Transmission Distance	328 feet (100 Metres)
Ethernet Standard	IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
Switching capacity	7.2G
Transfer Rate	14,880 pps @ 10Mbps / 148,800 pps @ 100Mbps / 1,488,000 pps @ 1000Mbps
MAC Address	4K MAC address table
Power Supply	Built-In Power Supply
Voltage Range	100~240 VAC
Power Consumption	200W for 16 PoE
Working Temperature	32°~104°F (0°~40°C) / 20~85% RH
Dimensions (W x H x D)	11.02" x 7.09" x 1.73" (280 x 180 x 44mm)