

VT-TPTZ5HR-2A4

1080p Indoor/Outdoor HD over COAX 4-IN-1 PTZ Mini Vandal Dome Camera with 5X Optical Zoom and IR LEDs [preliminary specs]



VITEKCCTV.COM
(888) VITEK-70




OVERVIEW

This HD over COAX Pan / Tilt / Zoom Mini Vandal Dome Camera features 5X optical zoom (2.7 ~13.5mm) and IR LEDs with a range of up to 65'. This Small and Attractive Pan Tilt Zoom Dome camera is vandal and weather resistant with an Infrared range beyond 65'. May be operated through Mobile and Client applications and programmed for patterns, tours and Auto pan.



KEY FEATURES

- 1/2.8" 2 MegaPixel Sony® CMOS Sensor
- 1080P output TVI, AHD, CVI / 960H CVBS
- Motorized 5 × Optical Zoom, f=2.7~13.5mm, Auto-Focus
- 2 IR LEDs with up to 65' IR Range
- Digital Wide Dynamic Range
- XD-DNR (3D-DNR & 2D-DNR)
- Pan Range: 0~350°, Pan Speed 45°/s, Tilt Range: 0~90°, Tilt Speed: 45°/s
- Built-in Surge and Lightning Protection
- 5 Tours
- DC12V Power
- Max 5W Consumption
- 3-Year Warranty

ACCESSORIES / DIMENSIONS



VT-TWMT-5PT
Wall Mount for 5" Surface PTZ
VT-TPTZ5HR-2A4



SPECIFICATIONS

Image Sensors	1/2.8" SONY® 2.0 Megapixel Progressive Scan CMOS Sensor
Effective Pixels	1920(H)×1080(V)
Synchronization	Internal
System	NTSC / PAL
Electronic Shutter	1/30s ~ 1/60,000s, 1/25s ~ 1/50,000s
Video Frame Rate	30fps / 25fps@1080P
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Video Output	1080P Output TVI, AHD, CVI / 960H CVBS
IR LEDs	Nano-tech IR LED: 42μ × 2pcs
IR Range	65' (20M)
Pan Range, Speed	0° ~ 350°, Horizontal, 45°/s
Tilt Range, Speed	0° ~ 90°, Vertical, 45°/s
Presets	255
Scan Mode	Auto Pan/Pattern/Auto Tour
PTZ Protocol	Pelco-D/Pelco-P and CoC (Control over COAX)
Baud Rate	2400 / 4800 / 9600 / 19200 / 38400
Focal Length	2.7 ~ 13.5mm
Aperture	F1.4
Lens Mount	M12
Focus / Zoom	AUTO / Motorized 5× Optical Zoom
Sense-Up	OFF/ON
WDR	D-WDR (Digital Wide Dynamic Range)
De-Fog	OFF/ON
BLC	OFF / BLC / HSBLC
White Balance	ATW / AWC-SET / Indoor / Outdoor / Manual / AWB
Day & Night	EXT / AUTO / COLOR / B/W
Noise Reduction	XD-DNR (2D-DNR & 3D-DNR)
Camera Title	OFF/ON
Motion Detection	OFF/ON
Privacy Mask	OFF/ON
OSD Language	English / German / French / Italian / Spanish / Polish / Russian / Portugese / Dutch / Turkish / Chinese
Ingress Protection	IP66
Power Supply	DC12V±10%
Power Consumption	Max 5W
Working Environment	14 ~ 122°F (10 ~ 50°C) / Less than 95% RH (no conden.)
Dimensions (Dia×Height)	4.33 × 3.56" / 110mm × 90.5mm



(888) VITEK-70 | WWW.VITEKCCTV.COM
28492 Constellation Road Valencia, CA 91355

An Eye On
Innovation