

# VTC-TNT4FL-2

Transcendent 4 MegaPixel Indoor/Outdoor  
Fixed Lens WDR IP Turret Camera



VITEKCCTV.COM  
(888) VITEK-70




## KEY FEATURES

- 1/2.7" 4.0 Megapixel CMOS Image Sensor
- Up to 30fps @ 4MP (2560 × 1440), 3MP (2304 × 1296), 1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
- 2.8mm Fixed Iris Lens
- Matrix IR with up to 100' IR Range
- Digital Wide Dynamic Range (D-WDR)
- True Mechanical Day/Night function by ICR
- XD-DNR (3D & 2D-DNR) Noise Reduction
- Built-in Mic\*
- Region Intrusion Detection, Scene Change Detection, Line Crossing, Object Removal, Video Blur Detection
- H.265, H.264 Compression
- MicroSD Card Slot for Local Recording (Up to 128GB)
- Remote Viewing via CMS, Internet Explorer, and iOS & Android Apps
- ONVIF Compliant
- IP67 Weather Resistance
- Optional Junction Boxes (VT-TJB08, VT-TJB01), Wall Mounts (VT-TWMT-3, VT-TWMT-A1), Pendant Mounts (VT-TPDMT-A1 [reqs. VT-TJB08], VT-TPDM-2 [reqs. VT-TJB01] available. See more below.
- 12VDC & PoE (Power over Ethernet) Operation
- 2-Year Warranty

## MOUNTS



**VT-TJB08**  
Optional  
Junction Box



**VT-TJB01**  
Optional  
Junction Box



**VT-TWMT3**  
Optional Wall  
Mount



**VT-TPDM-2**  
Universal 10"  
Pendant Mount.  
Reqs. VT-TJB01



**VT-TPDMT-A1**  
Universal 10"  
Pendant Mount.  
Reqs. VT-TJB08



**VT-TWMT-A1**  
Wall Mount. Reqs.  
VT-TJB08



**VT-TPLMT**  
Universal Pole  
Mount - Ivory, reqs.  
VT-TJB08



**VT-TCNMT**  
Universal Corner  
Mount - Ivory,  
reqs. VT-TJB08

## RECORDERS



Pair with VITEK Transcendent Series 6 and 8MP PoE NVRs in 4, 8, and 16 Ch. Configurations: VT-TNR414PL, VT-TNR818PL, VT-TNR1626PL

## SPECIFICATIONS

Image Sensor, Size	1/2.7" 4.0 Megapixel CMOS Image Sensor
Resolution	4MP(2560 × 1440), 3MP(2304 × 1296), 1080P(1920 × 1080), 720P(1280 × 720), D1, CIF, 480 × 240
Min. Illumination	0.011 lux @F1.2, AGC ON; 0 lux with IR, 0.04 lux @ F2.2, AGC ON; 0 lux with IR
Lens	2.8mm Fixed Iris Lens
Day / Night	True Day/Night by ICR
IR LEDs / IR Distance	1 Matrix / 100'
Video Compression	H.265 / H.264
Main-Stream	60Hz: 4MP/3MP/1080P (1~30fps), 50Hz: 4MP/3MP/1080P (1~25fps)
Sub-Stream	60Hz: 720P(1~15fps)/D1 /CIF (1~30fps), 50Hz: 720P(1~12fps)/D1 (1~25fps)/CIF (1~25fps)
Third Stream	60Hz: D1/CIF/480x240 (1~30fps), 50Hz: D1/CIF/480x240 (1~25fps)
Bit Rate	64Kbps ~ 12Mbps
Bit Rate Type	VBR / CBR
Other Camera Features	BLC, HLC, Defog
Wide Dynamic Range (WDR)	D-WDR (Digital Wide Dynamic Range)
Digital Noise Reduction (DNR)	XD-DNR (2D-DNR & 3D-DNR)
Image Setting	Saturation, Brightness, Chroma, Contrast, WDR, Noise reduction
Analytics	Object Removal, Scene Change, Video Blur Detection, Intrusion and Line Crossing
Smart Alarm	Motion Alarm, SD Card Error, SD Card Full
Region of Interest (ROI)	Each ROI to be Configured Separately
Network	RJ45
Audio	Built-in Mic*
Storage	MicroSD Card Slot (128GB)
Remote Viewing	CMS / Web Browser / Mobile (iOS/Android)
Supported Browsers	Microsoft Internet Explorer
Connection Protocol	ONVIF
Resistance	IP67 Weather Rating
Power Input	12VDC / PoE
Power Consumpt. (12VDC)	150mA (LEDs Off) / 320mA (LEDs On)
Power Consumpt. (PoE)	< 5W
Working Environment	-22° ~140° / < 95% Humidity
Weight	16.58 oz. / 1.04 lbs. / 460g
Dimensions: Dia × H	3.77" x 4.25" (95.7 × 108mm)

\*Please research local, state and federal laws regarding the implementation of audio surveillance.



(888) VITEK-70 | WWW.VITEKCCTV.COM  
28492 Constellation Road Valencia, CA

An Eye On  
Innovation